VISY-Command GUI

The control unit with a graphic display



VISY-Command GUI with printer

VISY-Command GUI contains the intrinsically safe power supply for the VISY-Stick sensors and their control unit. Various interfaces ensure that it always has access to the latest data. The integrated display unit with the 5.7" colour touch screen provides and displays the current measurement values and the reporting functions (log file) in a user-friendly form.
The VISY-Command GUI has a display with a clearly structured and easy to operate interface. The most important information, e.g. tank level and alarms are displayed directly and up-to-date on the screen. Using the touch screen, operators can call up detailed information simply by touching the tank graphics or the function keys.

Features of the FAFNIR technology

- Up to 3 different sensors can be connected to one terminal by a common cable.
- Up-to date overview of the tank contents shown at a graphic display
- Convenient tank content visualization with useful additional data, e.g. ullage
- Display of the tank contents in litres, with or without temperature compensation
- Display of product temperature and water level
- Highly flexible due to modular architecture
- Easy to upgrade and retrofit
- Precise configuration using the free software VISY-Setup
- Easy start-up
- Communication via Ethernet possible
- Free, user-friendly software for firmware updates
- Integrated alarm signal
- Wireless communication of VISY-Command GUI RF with VISY-Stick Sensors
- Optional with printer

Edition 05.2013 Technical changes reserved